

New Insights on the Structure of Electrochemically Deposited Li Metal and Its Solid Electrolyte Interphase via Cryogenic FIB & TEM

P.I. Y. Shirley Meng

Sustainable Power and Energy Center (SPEC)

Department of NanoEngineering

University of California San Diego

Project ID# bat 366

2018 DOE Vehicle Technologies Office Annual Merit Review

This presentation does not contain any proprietary, confidential, or otherwise restricted information

Overview

Timeline

- Project start date: December 2016
- Project end data: October 2021
- Percent complete: 30%

Budget

- Total project funding 50M
 - DOE share:100%
- FY2017 funding: 10M
- FY2018 funding: 10M

Barriers

- Abuse Tolerance: Li-metal based batteries have a long history of problematic dendrite growth
- Life: Cells containing Li metal anode still suffer major cycle and calendar life issues.
- **Performance**: Challenging "cold start" requirement at -30 °C.

Partners

- Battery500 and BMR
- PNNL, ARL and INL
- South 8 technology and Maxwell technology





Relevance/Objectives

□Overall objective

- -- Explore the nature of Li metal and its SEI
- -- Improve the cycle life of Li-metal based batteries at room and low temperature

□Objectives this period

- -- Quantify the structure of the electrochemically deposited Li metal (EDLi)
- -- Stabilize Li/electrolyte interface
- -- Explore novel electrolyte for low temperature use

□lmpact

- -- Bridge the gap between strategies and performance
- -- Accelerate the practical use of Li-metal based batteries
- -- Increase durability in low temperature environment




Milestones


Date	Milestones	Status
December 2017	Milestones: Develop stable electrolytes for room and low temperature use	Complete
March 2018	Milestones: Investigate the influence of the current density on Li metal	Complete
June 2018	Milestones: Establish the proper imaging and diagnosis of Li metal anode with different electrolytes and electrolytes additives	On track
September 2018	Milestones: Develop and implement methods to improve and understand cycles and calendar life of full cells	On track



Approach


- Develop cryogenic electron microscope (Cryo-EM) to image and diagnose the Li metal
- > Optimize the electrolyte to stabilize the interface between electrolyte and Li metal
- Quantify SEI components and "Dead" Li with advanced diagnosis methods











Scientific Gaps:


- 1. What is the true CE??? Depositing Li, Li₂O, Li₂CO₃, LiOH, LiF
- 2.Not all Li are the same Li Foil, Vapor Deposited Li (VDLi)and Electrochemically Deposited Li (EDLi)
- 3. Substrate/Separator/Electrolyte (Avoid studying things in vacuum)





1. Micro structure of Li metal film by Cryo FIB/SEM


Commercial Li metal

Room Temp (22 °C) Cryo (-170 ° C)











Severe beam damage and Ga contamination

Electrochemically deposited Li metal (EDLi)







1.2M LiPF₆ (3:7) EC:EMC, 0.5 mA/ cm²

Porous EDLi film














2. The critical need for Cryo TEM



Cryo TEM allows to image the Li metal at a high magnification with low doze.




Xuefeng Wang et. al. Nano Letters 2017



3. Nanostructure of electrochemically deposited Li EDLi


0.5mA/cm² for 5 minutes




Uneven SEI

Amorphous Li bulk

Crystalline LiF in SEI







Xuefeng Wang et. al. Nano Letters 2017




4. Atomic resolution imaging of EDLi

2.5mA/cm² for 30 minutes







Atomic structure of crystalline Li metal


Yuzhang Li, et. al. Science 2017







5. Additives lead to distinctive SEI





Amorphous Li bulk **Crystalline** LiF in SEI




6. Effect of current density on EDLi

Crystalline ED Li, Yuzhang Li, et. al. Science 2017

VS. 2.5mA/cm² for 30 minutes

Amorphous ED Li, Xuefeng Wang et. al. Nano Letters 2017 0.5mA/cm² for 5 minutes




Current density changes the crystallinity of Li metal and SEI properties



7. Improve EDLi by optimizing electrolyte

Relationship between Coulombic



1mAh/cm² = 5μ m/cm², so if you get 6μ m? Porosity in EDLi

Electrolyte with the higher CE results in the denser EDLi film.





Responses to Previous Year Reviewers' Comments

No reviewer comments are available from previous year review on this project.



Partners/Collaborators

Electrolyte provider and result discuss

Dr. Jason Zhang, Dr. Wu Xu, Dr. Jie

Xiao and Dr. Jun Lu (PNNL)

Dr. Kang Xu and Dr. Marshall

Schroder (ARL)

Dr. Boryann Liaw (INL)

> Cryo TEM facility

Dr. Elizabeth Villa (UCSD/Biological Sciences)

Dr. Xiaoing Pan (UC Irvine)

Liquefied gas electrolyte

Dr. Cyrus Rustmoji (South 8 Technology)

















Remaining Challenges and Barriers

- □ Correlation of a 'good' nanostructure of EDLi and high coulombic efficiency (CE)
- □ Determine the 'real' CE and quantify it
- Quantify the 'dead' Li and divide the percentage between chemically reacted Li and physically isolated Li metal
- ☐ In situ observe the plating and stripping process of Li metal by Cryo-TEM
- □ Construct a stable interphase between electrolyte and Li metal



Proposed Future Research

Key Challenges

- ➤ a 'good' nanostructure of EDLi
- Quantify the 'dead' Li
- In situ observation by cryo-TEM
- Stable interphase

Future work

- Comparing the nanostructure of EDLi from different conditions (electrolyte, additive, pressure)
- Quantify the dead metallic Li by titration and gas chromatography
- Design the cooling-bias holder
- Protect the Li metal with artificial or in-situ formed film
- Build Li metal based batteries

More team work will be incorporated in the future work

Any proposed future work is subject to change based on funding levels.






Future Team Work

Advancing High Energy Batteries by Design






Identifying Li Failure

Improving performance

- Fundamental issues related to the use of Li metal electrode directly impact full cell performance
- Failure mode & effect analysis: Advancing battery diagnostics and quantification of performance fade

 Multi-scale HPC simulation and analytics reconcile understanding of interfaces and cell designs



Current Density on Li metal electrode






Summary


Established cryogenic techniques to explore the nature of Li metal

Revealed the nanostructure of EDLi: amorphous Li and

crystalline LiF



Proposed liquefied gas electrolyte



FM based with 0.2M LiTFSI/LiFSI 25-50MPa

First cycle efficiency >92% Stabilizing efficiency >99.5%

